

APPENDIX 6 - STUDDED TYRES - DURING THE EVENT

January 31 - February 2, 2014

Pielikums Nr.6 – Riepas ar radzēm

Studded tyres may be used during the event. They must be in conformity with the following regulations:
Rallija laikā atļauts izmantot riepas ar radzēm, kas atbilst sekojošiem nosacījumiem:

- The studs shall be solid, cylindrical and flatcut.

Radzes drīkst būt stingras, cilindriskas un ar noapaļotiem galiem.

- The cross section of the studs must form a full circle at every point.

Radzes šķērsgriezumam jebkurā vietā jābūt pilnam aplim.

- The stud is not allowed to be tubular at any point.

Radze nevienā vietā nedrīkst būt cauruļveida.

- The body of the stud must be homogenous and is not allowed, under any circumstances to form a tube or hole. *Radzei jābūt viendabīgai, nav atļauts cauruļveida radzes.*

- Maximum diameter of the flange is 9 millimeters.

Maksimālais uzmalas diametrs ir 9 mm.

- Minimum diameter of the metal core in the middle of the stud is 2,5 millimeters. It must be cylindrical, homogenous and flatcut. *Minimālais metāla serdes diametrs radzes iekšpusē ir 2,5 mm.*

- The length of the stud is limited to 20 millimeters.

Maksimālais radzes garums ir 20 mm.

- The weight of the stud is limited to 4 grams.

Maksimālais radzes svars ir 4 grami.

- The studs must be mounted in to the tyres from the outside.

Radzēm jābūt iemontētām riepās no ārpuses.

- The number of studs must not exceed 20 per any decimeter of the wheel circumference.

Radžu skaits nedrīkst pārsniegt 20 radzes katrā riteņa perimetra decimetrā.

